Material Safety Data Sheet
May be used to comply with
OSHA's Hazard Communication Standard,
29 CFR 1910.1200. Standard must be
consulted for specific requirements

U.S. Department of Labor
Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

Identity (As used on label and list)
Val-Tex No. 75 & 75-S
75 - B, C, D, G, J, K, & V 75-S - all bulk packaging

Note: Blank spaces are not permitted. If any item is not applicable or no information is available, the space must be marked to indicate that.

Section I
Manufacturer's Name: Val-Tex (Valves Inc. of Texas)
Address: 10600 Fallstone Rd.
Houston, TX 77099

Emergency Telephone Number: (281) 530-4848
Telephone Number for Information: (281) 530-4848
Date Prepared: January 1, 2008
Signature of Preparer (optional)

Section II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s)	OSHA PEL	ACGIH TLV	Other Limits Recommended	%(optional)
None				

National Fire Protection Assn.: Hazards Rating Per Right-to-Know Laws are 0-0-0

HMIS Rating	Health	Flammability	Reactivity
	#0	#0	#0

Section III - Physical/Chemical Characteristics

Boiling Point:	N/A	Specific Gravity (H_20):	#75 @1.14 - #75-S @1.19
Vapor Pressure(mm Hg):	N/A	Dropping Point:	Over 500°F ASTM D-566
Vapor Density (Air = 1):	N/A	Evaporation Rate: (Butyl Acetate = 1)	N/A
Solubility in Water	Insoluble		
Appearance and Odor	Black - Slight Smell of Castor Oil		

Section IV - Fire and Explosion Hazard Data
Flash Point (Method Used) Over 500°F (C.O.C) Flammable Limits LEL: N/A UEL: N/A
Extinguishing Media: Water, Fog, Carbon Dioxide and Dry Chemical
Special Fire Fighting Procedures: Firefighters should wear self-contained apparatus in positive pressure mode with a full face piece when there is a possibility of exposure to smoke, fumes, or any decomposing products.
Unusual Fire and Explosion Hazards: None

Section V - Reactivity Data
Stability: Unstable Conditions to Avoid: Oxygen Service
Stable XXX
Incompatibility (Materials to Avoid): Oxygen Service - Strong Oxidizing Agents
Hazardous Decomposition or Byproducts: Unknown

Hazardous Polymerization: May Occur Will Not Occur XXX Conditions to Avoid: Avoid Contact With Strong Oxidizing Agents

Section VI - Health Hazard Data
Route(s) of Entry: Inhalation: Get In Fresh Air Skin: Prolonged Exposure May Cause Skin Irritation. Wash Affected Area With Soap and Water. Ingestion: If Swallowed, Call A Physician. Do Not Induce Vomiting.
Health Hazards (Acute and Chronic): As Noted
Carcinogenicity: None NTP: None ARC Monographs: None OSHA Regulated: None
Signs and Symptoms of Exposure: None
Medical Conditions Generally Aggravated by Exposure: None
Emergency and First Aid Procedures: If Swallowed - Do Not Induce Vomiting, Call A Physician.
Eye Contact - Flush with Plenty of Water and Call a Physician

Section VII - Precautions for Safe Handling and Use
Steps to Be Taken in Case Material Is Released or Spilled: Product is Non-Pourable - Follow All Federal, State, and Local Regulations Regarding Clean Up and Disposal.

Waste Disposal Method: Dispose of in Accordance With All Federal, State, and Local Regulations.
Precautions to be Taken In Handling and Storing: Normal Warehouse Storage
Other Precautions: None

Section VIII - Control Measures
Respiratory Protection (Specify Type): None
Ventilation : Local Exhaust : N/A Special : N/A Mechanical (General) : N/A Other : N/A
Protective Gloves: If Required Eye Protection: Safety Goggles, If Required
Other Protective Clothing Or Equipment: None
Work/Hygienic Practices: Use Standard Industrial Hygiene Practices When Handling Any Industrial Material.