

Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard,
29 CFR 1910.1200. Standard must be
consulted for specific requirements

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

Identity (As used on label and list)

Val-Tex 750 Stick and 750-S Bulk Lube Sealant
750 - A, B, C, D, G, J, K, & V 750-S - all bulk packaging

Note: Blank spaces are not permitted. If any item is not
applicable or no information is available, the space
must be marked to indicate that.

Section I

Manufacturer's Name: Val-Tex (Valves Inc. of Texas)
Address: 10600 Fallstone Rd.
Houston, TX 77099

Emergency Telephone Number: (281) 530-4848
Telephone Number for Information: (281) 530-4848
Date Prepared : January 1, 2008
Signature of Preparer (optional)

Section II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))		OSHA PEL	ACGIH TLV	Other Limits Recommended	%(optional) None
HMIS Rating	Health #1	Flammability #1	Reactivity #0		

Section III - Physical/Chemical Characteristics

Boiling Point:	N/A	Specific Gravity (H ₂ O):	750 @ 1.1409	750-S @ 1.1547
Vapor Pressure(mm Hg):	N/A	Dropping Point:	Over 500°F ASTM D-566	
Vapor Density (Air = 1):	N/A	Evaporation Date:	N/A	
		(Butyl Acetate = 1)		
Solubility in Water	Insoluble			
Appearance and Odor	Black			

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used)	395°F typical (C.O.C)	Flammable Limits	LEL: N/A	UEL: N/A
Extinguishing Media:	Water, Fog, Carbon Dioxide and Dry Chemical			
Special Fire Fighting Procedures:	Firefighters should wear self-contained apparatus in positive pressure mode with a full face piece when there is a possibility of exposure to smoke, fumes, or any decomposing products.			
Unusual Fire and Explosion Hazards:	None			

Section V - Reactivity Data

Stability: Unstable Conditions to Avoid: Oxygen Service
Stable XXX

Incompatibility (Materials to Avoid): Oxygen Service - Strong Oxidizing Agents
Hazardous Decomposition or Byproducts: Unknown

Hazardous May Occur Conditions to Avoid: Avoid Contact With Strong Oxidizing Agents
Polymerization: Will Not Occur XXX

Section VI - Health Hazard Data

Route(s) of Entry: Inhalation: Get In Fresh Air	Skin: Prolonged Exposure May Cause Skin Irritation. Wash Affected Area With Soap and Water.	Ingestion: If Swallowed, Call A Physician. Do Not Induce Vomiting.
Health Hazards (Acute and Chronic): As Noted	ARC Monographs: None	OSHA Regulated: None
Carcinogenicity: None NTP: None		
Signs and Symptoms of Exposure: None		
Medical Conditions Generally Aggravated by Exposure: None		
Emergency and First Aid Procedures: If Swallowed - Do Not Induce Vomiting, Call A Physician.		
Eye Contact - Flush with Plenty of Water and Call a Physician		

Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material Is Released or Spilled: Product is Non-Pourable - Follow All Federal, State, and Local Regulations Regarding Clean Up and Disposal.

Waste Disposal Method: Dispose of in Accordance With All Federal, State, and Local Regulations.
Precautions to be Taken In Handling and Storing: Normal Warehouse Storage
Other Precautions: None

Section VIII - Control Measures

Respiratory Protection (Specify Type): None
Ventilation : Local Exhaust : N/A Special : N/A Mechanical (General) : N/A Other : N/A
Protective Gloves: If Required Eye Protection: Safety Goggles, If Required
Other Protective Clothing Or Equipment: None
Work/Hygienic Practices: Use Standard Industrial Hygiene Practices When Handling Any Industrial Material.